

# LED LIGHT BAND ZEN XS

## OVERVIEW



Satin-finished acrylic glass,  
flush-mounted



Prismatic acrylic glass,  
flush-mounted



Satin-finished acrylic glass,  
surface-mounted

**Cover**

**Light colour**

3000 K / CRI > 80

4000 K / CRI > 80

**Unified Glare Rating**

UGR < 22

UGR < 25

**Luminous flux**

Medium

**Option**

DALI


Emergency operation<sup>1</sup>

DALI + Emergency operation<sup>1</sup>

	•	•	•
	•	•	•
		•	
	•		•
	•	•	•
	•	•	•


<sup>1</sup> With single battery supply 1 h, possible from a minimum length of 1135 mm.

## ACCESSORIES




No. 236986  
**End plate set ZR56/59  
ZEN XS**

Mains connection terminal and 2 end plates made of natural anodised aluminium, 43 x 60 x 2 mm, for flush-mounted cover.



No. 236987  
**End plate set ZR66  
ZEN XS**

Mains connection terminal and 2 end plates made of natural anodised aluminium, 43 x 70 x 2 mm, for surface-mounted cover.



No. 236988  
**End plate set ZR66  
ZEN XS**

Mains connection terminal and 2 end plates made of natural anodised aluminium / satin-finished acrylic glass, 43 x 70 x 3.5 mm, for surface-mounted cover.



No. 236989  
**Profile connector  
ZEN XS**  
Galvanised.



No. 236990S-1/2/3  
**Cable suspension**  
Galvanised, height adjustable. With ceiling part for screwing.



No. 236993  
**Corner connector ZR56  
ZEN XS**

Two-leg connecting element 90° of natural anodised aluminium profile 150 mm and cover 300 mm.



No. 236994  
**Corner connector ZR59  
ZEN XS**

Two-leg connecting element 90° of natural anodised aluminium profile 150 mm and cover 300 mm.



No. 236995  
**Corner connector ZR66  
ZEN XS**

Two-leg connecting element 90° of natural anodised aluminium profile 150 mm and cover 300 mm.

## OPTIONS ON REQUEST

- Colour temperature: 2,700 K, 6,500 K and Tunable White 2,700–6,500 K
- Colour rendering: CRI > 90
- Higher luminous flux
- Integrated sensors
- RAL/NCS paint finishes

### Reflector luminaire

Made up of a multicellular reflector. With universal mounting springs for ZEN XS profile.

- Colour temperature: 3,000 K and 4,000 K
- Colour rendering: CRI > 80 and > 90
- Reflector: white, matt black or high gloss
- Beam pattern: wide, narrow or asymmetrical

