

LED LIGHT BAND ZEN XS


OVERVIEW



Satin-finished acrylic glass,
flush-mounted



Prismatic acrylic glass,
flush-mounted



Satin-finished acrylic glass,
surface-mounted

Cover

Light colour

3000 K / CRI > 80

•

•

•

4000 K / CRI > 80

•

•

•

Unified Glare Rating

UGR < 22

•

UGR < 25

•

•

Luminous flux

Medium

•

•

•

Option

DALI

•

•

•

Emergency operation¹

•

•

•

DALI + Emergency operation¹


•

•

•


¹ With single battery supply 1 h, possible from a minimum length of 1135 mm.

ACCESSORIES




No. 236986
End plate set ZR56/59
ZEN XS

Mains connection terminal and 2 end plates made of natural anodised aluminium, 43 x 60 x 2 mm, for flush-mounted cover.




No. 236987
End plate set ZR66
ZEN XS

Mains connection terminal and 2 end plates made of natural anodised aluminium, 43 x 70 x 2 mm, for surface-mounted cover.



No. 236988
End plate set ZR66
ZEN XS

Mains connection terminal and 2 end plates made of natural anodised aluminium / satin-finished acrylic glass, 43 x 70 x 3.5 mm, for surface-mounted cover.



No. 236989
Profile connector
ZEN XS

Galvanised.



No. 236990S-1/2/3
Cable suspension
Galvanised, height adjustable. With ceiling part for screwing.

OPTIONS ON REQUEST

- Colour temperature: 2,700 K, 6,500 K and Tunable White 2,700–6,500 K
- Colour rendering: CRI > 90
- Higher luminous flux
- Integrated sensors
- RAL/NCS paint finishes

Reflector luminaire

Made up of a multicellular reflector. With universal mounting springs for ZEN XS profile.

- Colour temperature: 3,000 K and 4,000 K
- Colour rendering: CRI > 80 and > 90
- Reflector: white, matt black or high gloss
- Beam pattern: wide, narrow or asymmetrical

