

LICHT

tulux

SWISS LIGHT CREATIONS



PERL

PERL

OVERVIEW



Ceiling/wall Cable pendant Tube pendant

Light colour			
3000 K / CRI > 90	•	•	•
4000 K / CRI > 90	•	•	•
Light output			
Low	•	•	•
Medium	•	•	•
High (only Ø 400 mm and Ø 500 mm)		•	•
Cover			
Opal matt glass	•	•	•
Opal matt plastic	•	•	•
Unified glare rating			
UGR < 19	•	•	•
UGR < 22	•	•	•
Dimensions			
Ø 150 mm	•		
Ø 200 mm	•		
Ø 250 mm	•	•	•
Ø 300 mm	•	•	•
Ø 400 mm		•	•
Ø 500 mm		• (plastic only)	•
Control			
ON / OFF (only for ceiling/wall Ø 200 mm, Ø 250 mm and Ø 300 mm)	•		
DALI	•	•	•



Tube pendant



Ceiling

Other technical specifications:

- Effective luminous flux: 1017 to 7337 lm
- System efficiency: up to 141 lm/W
- Shock resistance: IK10 (plastic) / IK03; IK02 Ø 150 mm (glass)
- Photobiological safety: RG0 (BLH-A)
- IP class: IP20 / insect-proof lamp housing



← Scan the QR code
and discover all the highlights of the
PERL product family!

CUSTOMISATION

We can tailor your individual solution to suit your needs:

- Housing colour
 - Materials
 - Cover material
- Light output
 - Colour temperature
 - IP class
 - Surface-mounted cable routing

PERL – five convincing reasons.

1. Perfect globe shape
2. Floating elegance
3. Flawless workmanship
4. Uniform appearance
5. Variety of inspiring designs













TULUX AG
TÖDISTRASSE 4
CH-8856 TUGGEN
T +41 55 465 60 00
F +41 55 465 60 01
INFO@TULUX.CH

WWW.TULUX.CH



SLG 
member

